

Goes Where Your Eyes Can't!

The **HFIC-36 Flexible Inspection Camera** is designed to help you see around hard to reach areas that you couldn't normally reach in darkness or tight places. This tool features a 36" flexible camera with an LED illuminated tip. Included is a video out cable to hook up to a larger exterior monitor to get a more detailed image if desired, clip-on accessories and a rugged carrying case.

Features:

- **2.4"**, 320 X 240 Pixel Color LCD Monitor
- **Picture Rotation Capability**
- **Camera LED Illumination** (with brightness control)
- **Long Battery Life** (12 hrs using 4 x 1.5V AA)
- **Power and Low Battery Indicator LED**
- **NTSC Video Output for Remote TV Monitoring**
- **36"** Flexible, Waterproof Camera Tube
- **Clip-on Accessories: Mirror, Hook, Magnet**



HFIC-36
Inspection Camera
with 36" flexible camera tip



Clip-on Accessories
Hook, Magnet & Mirror



Carrying Case
Included

Specifications

2.4" TFT resolution	320 X 234 Pixels
Lens Sensor Resolution	320 X 240 Pixels
Sensitivity	0.7V (Lux.sec)
Color Mosaic	RGB Bayer Pattern
White Comparison	Automatic
Exposure to Light	Automatic
Video Format	NTSC Composite Video
Camera Illumination	2 LEDs, White
Handler End AVI Port	NTSC Signal Out
Power By	4 X 1.5V AA

Power Consumption	200 mA
Ambient/Operation Temperature	32° F to 113° F
TV Cable Length	55 inches
Total Length of Device	45.2 + - .75 inches
Metal Tube Length	34.6 + - .75 inches
Minimum Bending Radius	1.75 inches
Diameter of Camera Head	0.4 inches
Lens Coverage	54°
Short Distance Focus	1.1 - 2.3 inches