


ABS Coaxial Cable Product Type: TX15AT77-V (CATV) Black

Series 15 Coaxial Cable Copper Clad Aluminum Conductor Foamed Polyethylene Dielectric Bonded APA Laminate Shield 77% Aluminum Braid APA Laminate Shield Black PVC Jacket NEC 820 CATV Listed



Cable Ordering Information

Part Number	Description	NEC / CSA Listing
015T77V04BK2710000R1	TX15AT77-V (CATV) Black	NEC 820 CATV

Characteristics

Onaraotonotio			
Material	Detail	inches	mm
Inner Conductor	Copper Clad Aluminum	0.109	2.77
Dielectric	Foamed Polyethylene	0.455	11.56
1 st Outer Conductor	Sealed APA Tape	0.463	11.76
2 nd Outer Conductor	77% Aluminum Braid	0.490	12.45
3 rd Outer Conductor	APA Tape	0.494	12.55
Floodant			
Jacket	PVC, Flame Retardant, Black	0.595	15.11
Twisted Pairs			
Messenger			
Mechanical Specifications			
Minimum Bend Radius, in. (mm)		2.0	(50.80)
Product Weight	(less reel)	102 lbs /kft	

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: tx15at77-v (catv) black_1.8ghz18.docx

01.08.2019 Revision: Page: 1 of 2

uncontrolled copy

All Rights Reserved, Specifications subject to change without notice Amphenol Broadband Solutions

358 Hall Avenue Wallingford, CT 06492 Toll Free +1-800-677-2288 +1-434-432-1800 Toll Fax +1-434-432-1821 www.timesfiber.com



ABS Coaxial Cable Product Type: TX15AT77-V (CATV) Black

Electrical Specifications					
Impedance, Ω	75 ± 3				
Velocity of Propagation, %	88				
Capacitance, Nominal	15.5 pF/ft	50.9 pF/m			
DC Resistance	Ω / kft	Ω/km			
Inner Conductor	1.35	4.43			
Outer Conductor	2.69	8.83			
Loop	4.04	13.25			

Attenuation, Maximum @ 68 °F (20 °C)					
Frequency, MHz	dB / 100 ft	dB / 100 m			
5	0.21	0.69			
55	0.60	1.97			
211	1.16	3.81			
250	1.26	4.13			
270	1.31	4.30			
300	1.39	4.56			
330	1.45	4.76			
350	1.50	4.92			
400	1.61	5.28			
450	1.71	5.61			
500	1.80	5.91			
550	1.90	6.23			
600	1.98	6.50			
750	2.23	7.32			
870	2.41	7.91			
1000	2.59	8.50			
1100	2.72	8.92			
1200	2.84	9.32			
1218	2.85	9.35			
1300	2.96	9.71			
1400	3.07	10.07			
1500	3.17	10.40			
1600	3.28	10.76			
1700	3.38	11.09			
1794	3.46	11.35			
1800	3.47	11.38			

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: tx15at77-v (catv) black_1.8ghz18.docx

Revision: 01.08.2019 Page: 2 of 2

uncontrolled copy

All Rights Reserved,

Specifications subject to change without notice

Amphenol Broadband Solutions 358 Hall Avenue

Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com